

# The package `indextools`\*

Maïeul Rouquette<sup>†</sup>  
from Enrico Gregorio's work

## Contents

<b>1 Introduction</b>	<b>2</b>	5.1.5 Package <code>combine</code>	12
<b>2 Package usage</b>	<b>3</b>	5.2 Package <code>bidi</code>	12
<b>3 Specific package commands</b>	<b>4</b>	5.3 Index layout customisation	12
<b>4 If something goes wrong</b>	<b>8</b>	5.4 Index page customisation	13
<b>5 Hints</b>	<b>10</b>	5.5 Index location customisation	14
5.1 Conflicts	10	5.6 Using the <code>showidx</code> package	15
5.1.1 Two column typesetting and index prologue	10	5.7 Index List sectioning customisation	15
5.1.2 Class <code>memoir</code>	11	<b>6 Implementation</b>	<b>16</b>
5.1.3 Package <code>showidx</code>	12	6.1 Incompatibilities and emulation	17
5.1.4 Package <code>fancyhdr</code>	12	6.2 <code>\makeindex</code>	18
		6.3 <code>\index</code>	20
		6.4 <code>\printindex</code>	21
		6.5 'innote' and 'notenumber' options	27

## Abstract

This package is a fork of the `imakeidx` package. The original authors of `imakeidx` were Claudio Beccari and Enrico Gregorio; the first author withdrew his availability as a maintainer in 2013. The second author declined some upgrade suggestions to remove some incompatibilities with certain packages that are particularly important with critical editions dealing with languages that are being written from right to left. Therefore this fork, named `indextools`, was created by Maïeul Rouquette, who acknowledges the work of the two preceding authors thanking them for the excellent package they created; nevertheless this fork was necessary in order to let other users benefit from its functionalities very useful in the field of humanities.

We hope that one day, only one package will be provided. The differences with the `imakedix` are:

- the name;
- the compatibility with package `bidi`;
- this documentation.

---

\*Version number v1.7.0; last revision 2023/10/14.

<sup>†</sup>maieul at maieul dot net

This package replaces and extends the functionalities of `imakeidx`, therefore it **MUST** not be loaded at the same time as `imakeidx`. Some controls are implemented to avoid these situations; if loading of `indextools` is required after `imakeidx` is already loaded, it does not get loaded; at the same time, if it gets loaded, it sets a suitable macro so that `imakeidx` can't be loaded after `indextools`.

This package exploits the `\write18` facility of modern T<sub>E</sub>X system distributions that allows to run system commands while typesetting a document written with the L<sup>A</sup>T<sub>E</sub>X mark up. By so doing, the index or indices, that are usually typeset at the very end of the document, are possibly split and sorted so as to include them in the document itself. This process has some minor limitations: it's impossible to start an index before all other pages have been ejected.

For support, please open issues on:

<https://github.com/maieul/indextools>

## 1 Introduction

It's been some years now that the typesetting engine of the T<sub>E</sub>X system is just *pdf<sub>te</sub>x*; the original Knuthian *tex* is still corrected by D. E. Knuth himself, but is frozen, according to his will; it is still distributed by every T<sub>E</sub>X distribution, but in practice *pdf<sub>te</sub>x*, *xetex* or *luatex* are the most used interpreters and typesetting engines of most macro packages.

This program *pdf<sub>te</sub>x* was originally born with the facility of producing either a pdf output file, as its name suggests, or a dvi file. Since then it has been enriched with many upgrades, also with regard to the evolution of the PDF language itself. It also incorporates the extensions of  $\varepsilon$ -T<sub>E</sub>X and has the ability to open a shell so as to run system commands with their arguments. The same is true for *xetex* and *luatex*.

This facility, since the T<sub>E</sub>X Live 2010 distribution, is official, but is sort of restricted, in the sense that the T<sub>E</sub>X system configuration file contains a list of “safe” system commands that can be run by *pdf<sub>te</sub>x*; presently the only program relevant for this package is *makeindex*. This precaution is necessary in order to avoid running malicious code. Other programs can be run, though, but it's necessary to expressly tell *pdf<sub>te</sub>x* that it can do so; this authorisation is given by means of a suitable program option, as explained below.

This package will exploit this facility in order to run a perl script that is capable of splitting a raw index file into different chunks and to run the *makeindex* or *xindy* T<sub>E</sub>X system programs so as to sort and format the index entries according to a specified index style file. Once the shell is terminated, the typesetting program resumes its work and possibly prints the various formatted indices produced in previous steps. In this way the document indices are always synchronous with their document and no further typesetting runs are necessary.

In order to reach this goal, it is necessary that at least the restricted `write18` facility is enabled; if the T<sub>E</sub>X distribution in use does not enable this restricted feature by default, it is necessary to enable the typesetting engine to run such facility; depending on the distribution and the shell editor that is being used to work on a specific document, it is necessary to add `--shell-escape` (or `--enable-write18` for MiK<sub>T</sub>E<sub>X</sub>) to the command with which the typesetting program is launched, possibly through the shell editor. This applies to all three *pdf<sub>te</sub>x*, *xetex*, and *luatex*

typesetting engines.

If Lua<sup>A</sup>T<sub>E</sub>X is used and *luatex* is version 0.42 to 0.66, it's impossible to distinguish whether the restricted shell escape is active or not, so the automatic procedure will be tried anyway, unless disabled with the `noautomatic` package option. With version 0.68 or later, the behaviour is the same as with the other engines.

## 2 Package usage

This package is invoked as usual by means of a `\usepackage` command:

```
\usepackage[options]{indextools}
```

The available *options* consist in a comma separated list of the following options:

`makeindex` in order to use the *makeindex* sorting and formatting engine; this option is the default and is mutually exclusive with the three next options.

`xindy` in order to use the *xindy* sorting and formatting engine; `texindy` is an alias for `xindy` and actually it's the script *texindy* which is called by this package. Nevertheless if the real *xindy* is desired, in order to avoid the settings made up by *texindy*, so as to add *xindy* the command line specific settings, it is possible to specify the option `truexindy`; the user is then responsible to set up the *xindy* engine with the suitable command line options.

`upmendex` in order to use the *upmendex* sorting and formatting engine.

`xindex` in order to use the *xindex* sorting and formatting engine.

`noautomatic` disables the automatic splitting of the raw index files and running of the system programs; this option might be used to save time when one knows for sure that the index files are already OK and do not need to be refreshed. Actually the time spent in splitting, sorting and formatting is so short that this option might be useful only when very lengthy indices are being processed.

`nonewpage` inhibits the new page command to be issued when using an article type document class and multiple indices are being typeset. We don't see why someone would use multiple indices in an article (except possibly for package documentations, which usually provide a macro index and a list of changes).

`quiet` suppresses all messages about manual index processing.

`original` uses the class-provided `theindex` environment for typesetting the indices; it is implicitly set if the document class option `twocolumn` has been specified.

`afterindex` allows to use `\index` command after `\printindex`. In this case, the index will be printed only on the second run.

`innote` adds a mark for content indexed in note. The standard mark is an italic ‘n’ added after the page number. You can redefine the `\innote` command to modify the standard mark. The default value is:

```
\providecommand{\innote}[1]{#1\textit{n}}
```

`notenumber` adds the note number for content indexed in note. The standard marks is a ‘n.’ followed by the note number. You can redefine `\innotenumber` to modify the standard mark. The default value is:

```
\providecommand{\innotenumber}[2]{#2n.~#1}
```

`splitindex` calls the *splitindex* script by Markus Kohm, which is included in every TeX Live distribution since 2009. With this option all index entries, which are written in one raw index file, are successively split into all the requested index files; in this way there is virtually no limit on the number of indices that is possible to create for a particular document.

The last described option deserves an explanation. L<sup>A</sup>T<sub>E</sub>X can write on a limited number of files during a run, and some of these *output streams* are already reserved (among these: aux files, toc files, lof files, lot files, plus several other ones). When more than one index is produced, there’s the risk to run off the number of writable files, because normally `indextools` reserves an output stream for each index. So the `splitindex` option comes to rescue: with it only *one* raw index file is written out. At the first `\printindex` command, the program *splitindex* is called; it splits the large index file into as many parts as the number of requested indices; after this, *makeindex* or *xindy* can do their job. In this way only one output stream is needed during the L<sup>A</sup>T<sub>E</sub>X run.

When should you apply this option, then? With one index it’s useless, you should begin to consider it for two or more indices and definitely use it if you get the error message

```
! No room for a new \write
```

Apart from this case, with or without it, the results are the same. See section 4 to see what files are written during the L<sup>A</sup>T<sub>E</sub>X run with or without the option.

### 3 Specific package commands

As it is customary when just one index is produced, the standard L<sup>A</sup>T<sub>E</sub>X facilities, i.e. the commands `\makeindex`, `\index`, and `\printindex` must be used. This package redefines them so as to produce multiple indices and defines some other commands. The first three of the following commands may be used only in the preamble.

`\makeindex` with the syntax:

```
\makeindex[⟨key-values⟩]
```

where ⟨*key-values*⟩ is a comma separated list of key-value assignments of the form: **key=value**; the available keys are the following:

*name* is the symbolic name for an index; if this key is not specified, it defaults to the value of the `\jobname` control sequence, in other words the name of the current main `.tex` file, i.e., the file that `\inputs` and/or `\includes` all the files of the complete document. This symbolic name is necessary only when doing multiple indices and is used with the `\index` command to point to the right index.

Example: `name=nameidx`

*title* is the title that is typeset at the beginning of the specific index; if not specified, the `\indexname` value is used.

Example: `title=Index of names.`

*program* is the name of the system program that is used to sort and format an index; valid choices are *makeindex*, *xindy*, or *texindy*, plus *truexindy*, *upmendex*, *xindex*. If not specified the program specified among the package options is used. If no option is specified, *makeindex* is used. In order to use *xindy*, it's necessary to call *pdflatex* with the shell escape command line option.

Example: `program=xindy.`

*options* is the list of options to be passed to the sorting and formatting program; this list is a balanced text of program options, separated with the syntax required by the sorting and formatting program. For example, in order to use a different *makeindex* sorting and formatting style *mystyle.ist* and avoiding any message in the screen output, write `options=-s mystyle.`

*noautomatic* is a boolean key that defaults to **false**; you can set it to **true** by simply listing its key in the key-value list, without necessarily specifying the `=true` part. If specified the index sorting program won't be called during the typesetting run for this particular index.

*intoc* is a boolean variable that defaults to **false**; if you want to set it **true** you must simply list this key in the key-value list, with no need of specifying the `=true` part. By setting this key to **true** an entry for this particular index is put in the table of contents.

*columns* accepts an integer representing the number of columns in the index; this is silently ignored if the `original` or the `twocolumn` options are set; the number can even be 1.

Example: `columns=3`

*columnsep* accepts a dimension representing the separation between index columns; the default is 35 pt as in the standard classes.

Example: `columnsep=15pt`

*columnseprule* is a boolean option; if it is set, a rule will appear between the index columns.

`\indexsetup` with the syntax:

`\indexsetup{⟨key-values⟩}`

where again *⟨key-values⟩* is a comma separated list of `key=value` assignments; the available keys are:

*level* whose acceptable values are sectioning commands such as `\chapter` or `\chapter*`. Actually any command with an argument will do and will receive the index title as its argument. The default is `\chapter*` or, if the class doesn't provide chapters, `\section*`. If you specify `\chapter` so as to override the default starred command `\chapter*`, the index title goes directly to the table of contents; in this case do not specify the `intoc` option.

*toclevel* whose acceptable value is a sectioning command *name* such as `section` to indicate the level at which we want the indices appear in the table of contents.

*noclearpage* is a boolean option; when set, no `\clearpage` will be issued between indices. You might want to set it in order to have a 'chapter of indices'; in this case you are responsible for setting the right value of the above keys. For example

```
\indexsetup{level=\section*,toclevel=section,noclearpage}
...
\chapter*{Indices}
\printindex
\printindex[names]
\printindex[objects]
```

See more on this subject in [section 5](#)

*firstpagestyle* whose acceptable value is a page style, default `plain`. You might want to set it to `empty` or some other page style defined by the class or by yourself. This keyword is disabled when the package `fancyhdr` is loaded; any definition or choice of page styles must be done before typesetting the indices.

*headers* which takes two values: the left and right marks. You might want to use this for disabling automatic uppercasing, by saying, for example, `headers={\indexname}{\indexname}`; notice that these values should always be a pair of balanced braced texts. Don't use these keys if you use `fancyhdr`.

*othercode* whose acceptable value is arbitrary `TEX` code that will be executed at the beginning of index entries typesetting. For example you might want to change here the setting of `\parskip`.

`\splitindexoptions` must have as its argument the command line option to `splitindex`; this might be necessary on some systems. The default is `-m ""`, because we want it only for splitting the large index file into its components which are later processed by this package. See the `splitindex` documentation for other options.

`\index` with the syntax:

```
\index[⟨name⟩]{⟨entry⟩}
```

inserts *⟨entry⟩* in the raw index file named *⟨name⟩*; if only one raw index file

is being built in order to split it in different index files by means of *splitindex*, the  $\langle entry \rangle$  is listed in the specific slit index file with name  $\langle name \rangle$ ; if no name is specified, this  $\langle entry \rangle$  is added to the default index with name  $\backslash jobname$ . The  $\langle entry \rangle$  should be written according to the particular syntax of the sorting and formatting program.

$\backslash indexprologue$  with the syntax:

```
 $\backslash indexprologue[\langle spacing \rangle]{\langle text \rangle}$ 
```

is used to define some  $\langle text \rangle$  to go between the index header and the entries; the  $\langle spacing \rangle$  should be a vertical space command such as  $\backslash vspace\{36pt\}$  (default is  $\backslash bigskip$ ), controlling the spacing between the prologue and the index proper. The command affects only the next index produced by  $\backslash printindex$  and is best placed just before this command. Please read ahead for further information on the use of this command.

$\backslash printindex$  with the syntax:

```
 $\backslash printindex[\langle name \rangle]$ 
```

is used to typeset the particular index named  $\langle name \rangle$ ; if no optional argument is specified, the default index with name  $\backslash jobname.ind$  is typeset. Actually this command activates all the mechanism of closing the output to the raw index file, shelling out, possibly calling the *splitindex* script in order to divide the single raw file generated by the typesetting engine into distinct raw files according to the default or specified  $\langle name \rangle$ s for each index, calling the sorting and formatting program on each of these split raw files (unless inhibited by a *noautomatic* option; in which case a warning is issued in order to remember the typesetter that this particular index has not been processed), producing the sorted and formatted *.ind* files, and eventually inputs and typesets these formatted files. Deep breath.

Let's see an example. The sequence of commands

```
...
\usepackage{indextools}
...
\makeindex[title=Concept index]
\makeindex[name=persons,title=Index of names,columns=3]
...
\begin{document}
...
...relativity\index{relativity}...
...
... Einstein\index[persons]{Einstein, Albert}...
...
And this is the end of the story.

\printindex

\indexprologue{\small In this index you'll find only
  famous people's names}
\printindex[persons]
\end{document}
```

will produce two indices. Entries for either index must be typed as shown above. The prologue will be printed (full text width) only in the “Index of names”, which will be typeset in three columns.

When the `original` option is set, maybe implicitly because of `twocolumn`, `\indexsetup` and the keys `columns`, `columnsep` and `columnseprule` for `\makeindex` have no effect. Please read more on this matter further on.

## 4 If something goes wrong

Since `indextools` relies on good cooperation between package options and command line options for the  $\LaTeX$  run, in some cases it may happen that the indices are not correctly built or built at all.

If you use only `makeindex` and  $\TeX$  Live 2010 or later, then you shouldn't need anything special, since `makeindex` is among the safe programs allowed to be called during a  $\LaTeX$  run, be it `latex`, `pdflatex`, `xelatex`, or `lualatex`.

When the options `splitindex`, `xindy`, `texindy` or `truexindy` are specified (globally or locally), the  $\LaTeX$  run should be called with the unrestricted `--shell-escape` (which is `--enable-write18` for  $\text{MiK}\TeX$ ) typesetting program option or the `noautomatic` option should be specified when loading `indextools`.

Let's look at a couple of examples. In both we suppose that the document `mybook.tex` defines two indices through

```
\makeindex[...]  
\makeindex[name=secondary,...]
```

where `...` denotes possible options excluding `name`.

First of all we examine the case when `indextools` is called *without* `splitindex`. Two files called `mybook.idx` and `secondary.idx` will be written during the  $\LaTeX$  run. At the corresponding `\printindex` command, `makeindex` will act on each of them producing the files `mybook.ind`, `mybook.ilg`, `secondary.ind` and `secondary.ilg`. The `.ind` files contain the relevant `theindex` environments with alphabetised entries, while in the `.ilg` files `makeindex` will write its log. You can check in `mybook.log` whether the `makeindex` run has been executed by searching for a line

```
runsystem(makeindex <...>)...executed
```

where `<...>` stands for the rest of the command line in the particular case. If this line is not present, then `makeindex` has not been called; this happens when you didn't specify the shell escape command line option for the  $\LaTeX$  run or the restricted shell escape is not active; also, of course, if you set the `noautomatic` option for the index.

When using `splitindex`, the situation is different. During the  $\LaTeX$  run, only a large index file called `mybook.idx` file gets written; the first `\printindex` command will call `splitindex` (unrestricted shell escape *must* be active), which will produce the two partial index files `mybook-mybook.idx` and `mybook-secondary.idx`. These two files will be processed by `makeindex` producing the four files `mybook-mybook.ind`, `mybook-mybook.ilg`, `mybook-secondary.ind` and `mybook-secondary.ilg`. The line

```
runsystem(splitindex <...>)...executed
```



	<code>\makeindex</code>	<code>\makeindex[name=secondary]</code>
	without <code>splitindex</code>	with <code>splitindex</code>
(at <code>\begin{document}</code> )	<code>mybook.idx</code> <code>secondary.idx</code>	<code>mybook.idx</code>
(at <code>\printindex</code> )	<code>mybook.ind</code> <code>mybook.ilg</code> <code>secondary.ind</code> <code>secondary.ilg</code>	<code>mybook-mybook.idx</code> <code>mybook-secondary.idx</code> <code>mybook-mybook.ind</code> <code>mybook-mybook.ilg</code> <code>mybook-secondary.ind</code> <code>mybook-secondary.ilg</code>

Table 1: Files written during a L<sup>A</sup>T<sub>E</sub>X run

in `mybook.log` will tell that the splitting has been done (see later on if this doesn't seem true). In table 1 you can see what files are produced when the first two lines are in the preamble.

Everything is the same when using *texindy* for alphabetising, except that, by default, it doesn't write `.ilg` files. If you want them, add `options=-t <name>.ilg` to the relevant `\makeindex` command, in our example it should be

```
\makeindex[...options=-t mybook.ilg]
\makeindex[name=secondary,...options=-t secondary.ilg]
```

The name of the `.ilg` file *must* be specified. Remember, though, that *xindy* `.ilg` files may turn out to be very large.

When something different from expected appears to take place, check also the time stamps of the produced files; if they are older than `mybook.log`, it means that they have not been written in the last run. The most common case is that you forgot to activate the shell escape feature (which is not necessary with T<sub>E</sub>X Live 2010 or later, provided you use only *makeindex*).

Another cause of malfunction might be a wrong option passed to *makeindex*, *texindy* or *splitindex*. For example, if you specify a style option for *makeindex* such as `options=-s mystyle.ist` and the style file is missing or its name is mistyped, the run of *makeindex* will result in `mybook.log`, but it will be aborted and the T<sub>E</sub>X program has no control over this process. In this case the `.ilg` and `.ind` files will not be produced and you can spot the problem by checking the time stamps. On some systems a message such as

```
Index file mystyle.ist not found
Usage: makeindex [-ilqrcgLT] [-s sty] [-o ind] [-t log] [-p num]
```

may appear on the screen, but often this window gets closed before you realize you have a problem. The time stamp is the best clue to detect such problems.

Shell hackers may be able to redirect the `stderr` stream to a file, but this requires skills that can't be explained here, because they require tens of different

tricks, depending on what method is used to start a L<sup>A</sup>T<sub>E</sub>X run. From the command line, assuming *bash*, it would be something like

```
pdflatex --shell-escape mybook.tex 2>latex-errors
```

If shell hackers know a way to access the exit status of the called program, we'd be glad to implement a supplementary check.

## 5 Hints

Actually this package reaches two goals: (*a*) it typesets the indices of a specific document in just one run, and (*b*) it lets the author/typesetter produce documents with multiple indices.

### 5.1 Conflicts

#### 5.1.1 Two column typesetting and index prologue

As it has been already mentioned, it is possible to use the command `\indexprologue` to write some text before the index proper gets typeset; an optional space may be used in place of the default one-line spacing between the index title, the prologue and the index body.

This facility relies on a particular feature of the `multicols` environment, that `indextools` uses to instruct the typesetting program to typeset the index with a specified number of balanced columns. The choice of `multicols` has been made because it balances the columns in the last page; the declaration `\twocolumn` does not perform the same way, and, if used, it makes `\printindex` typeset the index in two-column mode with an unbalanced last column.

In the previous sections it has been clearly stated that any configuration of the way `indextools` typesets the indices is bypassed if the option `original` has been specified either explicitly or implicitly. It is implicitly specified if the option `twocolumn` is specified in the class declaration statement.

Why? Because if two column typesetting is desired for the whole document, it is not clear if the index has to be typeset in one column within each column of the document, or if it should be typeset in two column mode after a `\onecolumn` command is being issued; the results are not the same: with the former method the columns remain unbalanced, while the latter has balanced columns. Furthermore the `\onecolumn` command forces a page break; without the `\onecolumn` command if the index is treated as a chapter, there is a page break, while if it is configured to be typeset as a section there is no forced page break. With this plethora of combinations we decided to avoid any configuration of the index typesetting and left the decision to the user. This requires the user to practice some ingenuity in order to obtain what he expects.

First of all the user shall not specify the `twocolumn` option to the class. Secondly the user asks for the use of `indextools` and sets up the single or multiple `\makeindex` commands. thirdly he loads all other packages required for his document; possibly he uses also `geometry` in order to specify a specific page layout. He shall specify the `\twocolumn` declaration after the above has been completed, in any case after the `indextools` package has been loaded and the single or multiple `\makeindex` commands are configured.

A good example might be this one:

```
\documentclass[a4paper,11pt]{book}
\usepackage{indextools}
\indexsetup{level=\section*,toclevel=section,noclearpage}
\makeindex[title=Index of places,columns=1]
\twocolumn
\usepackage[T1]{fontenc}
\usepackage{lmodern}
\usepackage[italian,english]{babel}
\usepackage[utf8]{inputenc}
\usepackage[a4paper,margin={1in,1in},binding=3mm]{geometry}
\usepackage[english]{varioref}
\usepackage[hang]{caption}
\begin{document}
...
\indexprologue{This index lists all the residences where Lady Esther
lived during the time span described in the book.}
\printindex
\end{document}
```

In this way the index is typeset as a “section”, not as a “chapter”, in one column mode within the two column document style; the indicated prologue is typeset between the index title “Index of places” and the start of the index proper.

On the opposite the following code:

```
\documentclass[a4paper,11pt]{book}
\usepackage{indextools}
\makeindex[title=Index of places,columns=2]
\twocolumn
\usepackage[T1]{fontenc}
\usepackage{lmodern}
\usepackage[italian,english]{babel}
\usepackage[utf8]{inputenc}
\usepackage[a4paper,margin={1in,1in},binding=3mm]{geometry}
\usepackage[english]{varioref}
\usepackage[hang]{caption}
\begin{document}
...
\onecolumn
\indexprologue{This index lists all the residences where Lady Esther
lived during the time span described in the book.}
\printindex
\end{document}
```

produces an index typeset as a “chapter”, starting on a new page; it is typeset in two balanced columns. The prologue is typeset where it should. The ingenious reader can experiment mixing the various settings used in these two examples in order to find out what benefits or disadvantages one can obtain with settings that are not physically impossible, but that may be aesthetically conflicting with one another.

### 5.1.2 Class *memoir*

The first public version of this package was not compatible with the *memoir* class. Since version 1.1 it is; however, one has to keep in mind that all index processing is

done with the methods of the present package, and *not* with `memoir`'s; however the syntax used is the same and there should be no problem. There is an interaction between `memoir` and `showidx` that required special attention. See below about using `showidx`.

### 5.1.3 Package `showidx`

Up to version 1.1 this package did not allow to use it together with the `showidx` package; now it is, provided that `showidx` is loaded *before* `indextools`. See below more information on using `showidx`.

### 5.1.4 Package `fancyhdr`

When using package `fancyhdr` some inconveniences did show up; now we believe we have detected the causes and we implemented the necessary corrections<sup>1</sup>.

### 5.1.5 Package `combine`

Apparently there might be some conflicts with package `combine`, because this package redefines the contents of `\jobname`; we tried to control this behaviour, and made the necessary patches, but it is still necessary to load this package `indextools` *before* package `combine`.

## 5.2 Package `bidi`

A strange conflict was discovered between packages `imakeidx` and `bidi`, in order to let `hyperref` redefine some internal macros so as to have index hyperlinks properly executed. This implies that the “index” package be loaded before `hyperref`; on the opposite `bidi` (for bidirectional writing, needed for typesetting Arabic and Hebrew scripts, among other ones) *must* be loaded after `hyperref` and redefines some hyper commands that have influence on the indexing package; therefore after loading `bidi` the previous redefinitions are lost. A solution was found by modifying the definition of the environment `theindex` and delaying its definition to the execution of `\begin{document}`. This is the main reason of this fork so that `indextools` may be loaded, as most packages normally do, before `hyperref`.

## 5.3 Index layout customisation

If you redefine yourself the `theindex` environment, please remember not to number the chapter or section that introduces the index if you ask for the `intoc` option; either use the commands `\chapter*` or the `\section*` respectively and the `intoc` option or don't use this option and redefine your `theindex` environment with numbered chapter or section commands, that will put the index titles directly into the table of contents. See below the effect of the `\backmatter` declaration. You may use the `idxlayout` package by Thomas Titz, which offers many functions for index typesetting customisation and is compatible with our package; remember to load `idxlayout` after `indextools`. This package has a similar function to our `\indexprologue`, called `\setindexprenote`; however `idxlayout` doesn't reset the

---

<sup>1</sup>Thanks to Maïeul Rouquette who, before creating this fork, spotted the problems and suggested some patches.

index prologue, which must be declared anew or disabled with `\noindexprenote` before the next `\printindex` command. In any case take into serious consideration what is being said hereafter about customisation.

## 5.4 Index page customisation

The same, more or less, holds true if you customise your headings; `indextools` can deal with standard settings, but it generally cannot deal with personal styles and customisations. This is why if you load `fancyhdr`, some of the `\indexsetup` settings may be disabled.

When you make any kind of customisation, remember that there are several classes, or personal settings, or features that may render your customisation very difficult to handle. Typically:

- There are classes where the normal usable highest sectioning command, disregarding `\part`, is not `\chapter`, but `\section`; for example classes *article*, *scrartcl*.
- Sectioning commands come in two varieties: starred and unstarred; the former ones are not numbered and do not produce any entry in the headings and in the table of contents; the latter ones may behave differently according to the next item.
- There are some classes (for example *book*, *scrbook*, *memoir*,...) that have the special “sectioning” declarations `\frontmatter`, `\mainmatter`, and `\backmatter` which modify how the unstarred sectioning commands behave for what concerns the heading and the table of contents entries.

For what concerns indices, these are generally typeset at the document end. This means that the `\backmatter` declaration may be in force; in this case unstarred sectioning commands are not numbered but they produce normal headings and table of contents entries.

- Heading entries are used by the output routine paging algorithm in such a way as to extract the left or the right part from suitable “marks”; for the even (left) pages the required information is extracted from the `\topmark` or `\firstmark`, while for the odd (right) pages they are extracted from the `\botmark`. Generally speaking, the even page heading refers to `\leftmark` and odd page headings refer to `\rightmark`; these are the two commands that extract the correct part from the suitable marks. But when you use the *headers* option value, you specify two brace balanced strings that are loaded through `\markboth` as the left and right part of the current mark.
- The contents of the marks may be very varied; they are generally made up of two brace balanced strings, which in turn may contain other brace balanced strings that may be used in different ways by the selected page style and by the page style definitions of the macros `\chaptermarks`, `\sectionmarks`, and `\subsectionmarks` that may interfere with personal customisations.
- Remember also that things change in an obvious way when one side typesetting is chosen; all pages are treated as if they were odd ones; therefore any customisation must take into account also this aspect.

The above list has not been written down for discouraging customisations of any kind: simply it recalls what must be taken care of in order to create one's customisation in a proper way.

The above list explains why we disabled the commands tied to the `\indexsetup` keys `headings` and `firstpagestyle` when package `fancyhdr` is being used; you may even set up these keys, but if the `fancyhdr` package has been loaded, we disable their action; this implies that any fancy customisation must be done before starting to print any index.

The `intoc` option must also be used with care, as well as the starred or unstarred sectioning commands for the `level` and `toclevel` option values. They must be chosen according to what the possible `\backmatter` declaration sets up, in order to avoid double entries in the table of contents; the `\backmatter` settings may also influence the way heading information is being used, and this makes it even more stringent to set up any index page style customisation before starting to print any index.

Therefore if by chance you get double entries into the table of contents, eliminate the `intoc` option from your calls; your class, packages, and settings are already taking care of it.

The package `tocbibind` should be loaded with the `noindex` option, otherwise it would interfere with our redefinition of `theindex`.

If you redefine your `theindex` environment by means of other packages, pay attention that these redefine a real `theindex` environment with this very name; if they create an environment with a different name, `indextools` can't take care of the indices production (in particular the  $\TeX$  system program `makeindex` creates a sorted and formatted `.ind` file that refers explicitly to the `theindex` environment), and it can't take care of the table of contents entry and of the position of the hyper link anchors needed to navigate your document by means of hyper links.

## 5.5 Index location customisation

Some packages might want to use the facilities of `indextools` to offer customised index commands, where the entry location is not expressed by a page number, but by an other reference value (for example: line number, entry number, etc.).

These packages may use the low-level command `\indtl@wrindexentry` which takes three arguments:

1. The index name.
2. The entry.
3. The location number.

For example `\indtl@wrindexentry{names}{Charles}{26}` adds to the index `names` the value `Charles` with the location reference `26`.

In simpler words, the new command `\indtl@wrindexentry` is of interest mainly to package and class authors; it is not to be used by the "normal" user, who, on the opposite, if interested in referencing the index entries on some location counter different from the page one, is urged to refer to the classes and packages that implement this facility; `eledmac` should be one of these packages. Matter of fact this addition to the `indextools` package was contributed by Maïeul Rouquette, the author and maintainer of `eledmac`.

## 5.6 Using the showidx package

If you want to make use of the `showidx` facilities, remember to load that package *before* `indextools`; remember also to disable or comment out the call to `showidx` when you typeset the final version of your document. This constraint is due to the fact that `showidx` redefines several internal commands, some of which have to receive the `indextools` definition in order to perform as described in this documentation.

At the same time if the `memoir` class is being used, remember that this class simulates the `showidx` package and has its own commands to enable or disable the printing of the index entries into the margin of the document; the default setting is with the `\hideindexmarks` command in force; but if the user wants to write his index entries in the margin he has to issue the declaration `\showindexmarks` just after `begin document`, in any case before the part of the source file(s) he wants to be marked with the index entries in the margin.

## 5.7 Index List sectioning customisation

Use freely the options and the key values in order to reach the desired results, but you are advised to prepare in advance the styles for composing the various indices in a proper way; for example, if you use a titled style for the index, where the index sections are distinguished with a bold face title or alphabetic letter, you have to set up a `.ist` file, such as `myindexstyle.ist`, made up like this:

```
headings_flag 1
heading_prefix "\\par\\penalty-50\\textbf{"
heading_suffix "}\\\\\\\\*~\\\\\\\\*"
symhead_positive "Symbols"
symhead_negative "symbols"
numhead_positive "Numbers"
numhead_negative "numbers"
delim_0 ",\\~"
```

where the numeric and non alphabetic entries have different titles. But, say, you are making also an index where the entries are file names, and for some names only the extension is entered; the extensions start with a dot, so the sorting program will sort these names at the beginning of the sorted index file, but you won't like to have a title such as "Symbols"; you probably prefer to have a title such as "Extensions"; therefore you have to prepare a different index style file, such as this one:

```
headings_flag 1
heading_prefix "\\par\\penalty-50\\textbf{"
heading_suffix "}\\\\\\\\*~\\\\\\\\*"
symhead_positive "Extensions"
symhead_negative "extensions"
numhead_positive "Numbers"
numhead_negative "numbers"
delim_0 ",\\~"
```

This done, besides requiring the use of this package, you have to declare the `\makeindex` command with the necessary options; pay a particular attention to the options that involve the index symbolic name, the index title, the index style, the fact that the index titles shall appear in the table of contents, and if you

are preparing an e-book, you probably would like to hyper link both the page numbers and the index titles to the proper locations. The typesetting program will do everything for you but be careful not to confuse it with illogical index entries.

Especially with multiple indices it is important that you are consistent in putting the right information in the right index and with a consistent mark-up. Define yourself appropriate macros so that, for example, personal names are consistently typeset, say, in caps and small caps and are entered into a specific index; you may even create one command to typeset the name in the document and replicate the same name in the index.

Of course there is no program that can decide at your place what and where to index each piece of information; this is a task for humans. Soooooo...

HAPPY T<sub>E</sub>XING!

## 6 Implementation

The heading to the file is in common with the documentation file, and has already been taken care of. But we require the `xkeyval` package, in order to handle the key-value lists.

Notice that in order to create a specific name space so as to avoid possible conflicts with other packages, all the commands defined in this package are prefixed with the string `indtl@`.

```
1 \RequirePackage{xkeyval}
```

We define the various options and their defaults. After `\ProcessOptions`, we set anyway the `original` option if the document class has been given the `twocolumn` option, which is incompatible with `multicol`. We define also an internal alias for `\immediate\write18`, a rudimentary check for the typesetting engine and a macro for modifying the command line call to `splitindex`. The `xpatch` is requested; at the moment none of its features are used, but it calls `etoolbox`, whose facilities are used here; while future extensions will benefit from the extended patched commands, that strongly enrich the performances of the main package `etoolbox`.

```
2 \DeclareOption{xindy}{\def\indtl@progdefault{texindy}}
3 \DeclareOption{texindy}{\def\indtl@progdefault{texindy}}
4 \DeclareOption{truexindy}{\def\indtl@progdefault{truexindy}}
5 \DeclareOption{makeindex}{\def\indtl@progdefault{makeindex}}
6 \DeclareOption{upmendex}{\def\indtl@progdefault{upmendex}}
7 \DeclareOption{xindex}{\def\indtl@progdefault{xindex}}
8 \newif\ifindtl@disableautomatic
9 \DeclareOption{noautomatic}{\indtl@disableautomatictrue}
10 \newif\ifindtl@nonewpage
11 \DeclareOption{nonewpage}{%
12   \indtl@nonewpagetrue\indtl@disableautomatictrue
13 }
14 \newif\ifindtl@splitindex
15 \DeclareOption{splitindex}{\indtl@splitindextrue}
16 \newif\ifindtl@original
17 \DeclareOption{original}{\indtl@originaltrue}
18 \DeclareOption{quiet}{\AtEndOfPackage{%
19   \let\indtl@finalmessage@gobble
```



```

20 \let\indtl@splitindexmessage\relax}}
21 \newif\ifindtl@afterindex
22 \DeclareOption{afterindex}{\indtl@afterindextrue}
23
24 \newif\ifindtl@innote
25 \DeclareOption{innote}{\indtl@innotetrue}
26
27 \newif\ifindtl@notenumber
28 \DeclareOption{notenumber}{\indtl@notenumbertrue}
29
30 \ExecuteOptions{makeindex}
31 \ProcessOptions\relax
32
33 \if@twocolumn\indtl@originaltrue\fi
34 \def\indtl@exec{\immediate\write18}
35 \def\indtl@engine{(pdf)latex}
36 \RequirePackage{ifxetex,ifluatex}
37 \ifxetex\def\indtl@engine{xelatex}\fi
38 \ifluatex % luatex doesn't have \pdfshellescape
39 \def\indtl@engine{lualatex}
40 \ifnum\luatexversion<68
41 \chardef\indtl@shellescape\@ne % no way to know the value
42 \else
43 \RequirePackage{pdftexcmds} % provides \pdfshellescape
44 \chardef\indtl@shellescape\pdfshellescape
45 \fi
46 \let\indtl@exec\pdf@system
47 \fi
48 \RequirePackage{xpatch}
49 \edef\indtl@splitindexoptions{-m \string"\string"}
50 \def\splitindexoptions#1{\g@addto@macro\indtl@splitindexoptions{ #1}}
51 \@onlypreamble\splitindexoptions

```

## 6.1 Incompatibilities and emulation

While experimenting we found out that some classes or packages are either incompatible with this one, or must be faked in order to pretend they have been loaded.

There is a serious incompatibility with the `memoir` class. In fact `memoir` puts all index entries in the main `.aux` file and extracts them to the various raw index files at `\end{document}` time. This means that no raw index file output stream has been defined, and therefore this package can't close it; moreover it can't typeset the indices before `\end{document}` because they are not yet available. Therefore if `memoir` is the active class, we will hijack its index mechanism replacing it with ours.

On the opposite we pretend that package `makeidx` or package `multind` have been loaded, so that `hyperref` can play with their commands, that are substantially the same as those used here. By so doing those packages are inhibited from being loaded after this one. We do the same with the forked original `imakeidx` package so that if `imakeidx` is loaded before, `indextools` is not loaded, but an error message is issued; otherwise we fake the fact that `imakeidx` has already been loaded so that it does not get reloaded.

```

52 \@namedef{ver@makeidx.sty}{3000/12/31}
53 \ifpackageloaded{multind}
54   {\PackageError{indextools}{Incompatible package ‘multind’ loaded}
55     {This package is incompatible with multind, don’t load both.%
56     \MessageBreak\@ehc}}
57   {\@namedef{ver@multind.sty}{3000/12/31}}
58
59 \ifpackageloaded{imakeidx}
60   {\PackageError{indextools}{Incompatible package ‘imakeidx’ loaded}
61     {This package is incompatible with imakeidx, don’t load both.%
62     \MessageBreak\@ehc}}
63   {\@namedef{ver@imakeidx.sty}{3000/12/31}}

```

At the same time we redefine some commands defined by `makeidx` and we define the default English names for the `\see` and `\seealso` commands. We use `\providecommand` so that, if `makeidx` has already been loaded, we do not redefine things that have already been defined.

```

64 \providecommand*\see[2]{\emph{\seename} #1}
65 \providecommand*\seealso[2]{\emph{\alsoname} #1}
66 \providecommand*\seename{see}
67 \providecommand*\alsoname{seeupmindex also}

```

## 6.2 `\makeindex`

From here on, some commands are duplicated; this depends on the fact that the behavior must be different when using `splitindex` or not. The memory occupied by the useless commands will be cleared at the end of package.

```

68 \providecommand*\makeindex{} % to use \renewcommand safely
69 \renewcommand{\makeindex}[1][\indtl@makeindex]{#1}
70 % \@onlypreamble\makeindex % Already in latex.ltx

```

This package implementation of `\makeindex` sets default values for the keys, then evaluates its argument (which is the optional argument to `\makeindex`) and calls two other macros. After that we have to reset the defaults.

```

71 \def\indtl@makeindex#1{%
72   \edef\indtl@name{\jobname}%
73   \edef\indtl@jobname{\jobname}%
74   \def\indtl@title{\indexname}%
75   \edef\indtl@program{\indtl@progdefault}%
76   \let\indtl@options\space
77   \KV@indtl@noautomaticfalse\KV@indtl@intocfalse
78   \setkeys{indtl}{#1}%
79   \ifindtl@splitindex\KV@indtl@noautomaticfalse\fi
80   \indtl@build\indtl@name
81   \indtl@startidx\indtl@name
82   \indtl@resetdefaults
83 }

```

Here are the keys. As usual, the `indtl@` prefix is used to distinguish anything that is being defined in this package, even the keys.

```

84 \define@key{indtl}{name}{\def\indtl@name{#1}}
85 \define@key{indtl}{title}{\def\indtl@title{#1}}
86 \define@choicekey{indtl}{program}[\indtl@val\indtl@nr]
87 {makeindex,xindy,texindy,truexindy,upmindex,xindex}{%

```

```

88   \ifcase\indtl@nr\relax
89     \def\indtl@program{makeindex}%
90   \or
91     \def\indtl@program{texindy}%
92   \or
93     \def\indtl@program{texindy}%
94   \or
95     \def\indtl@program{xindy}%
96   \or
97     \def\indtl@program{upmendex}%
98   \or
99     \def\indtl@program{xindex}%
100  \fi}
101 \define@key{indtl}{options}{\def\indtl@options{ #1 }}
102 \define@boolkey{indtl}{noautomatic}[true]{}
103 \define@boolkey{indtl}{intoc}[true]{}
104 \define@key{indtl}{columns}{\def\indtl@columns{#1}}
105 \define@key{indtl}{columnsep}{\def\indtl@columnsep{#1}}
106 \define@boolkey{indtl}{columnseprule}[true]{}
107 \def\indtl@resetdefaults{%
108   \def\indtl@options{ }%
109   \def\indtl@columns{2}\def\indtl@columnsep{35\p}%
110   \KV@indtl@columnseprulefalse
111   \KV@indtl@intocfalse\KV@indtl@noautomaticfalse}
112 \indtl@resetdefaults

```

The control sequence `\indtl@build` defines a control sequence to hold the setup for an index to be used when the index is sorted and printed

```

113 \def\indtl@build#1{%
114   \toks@{}%
115   \indtl@dokey\indtl@title
116   \indtl@dokey\indtl@program
117   \indtl@dokey\indtl@options
118   \indtl@dokey\indtl@columns
119   \indtl@dokey\indtl@columnsep
120   \ifKV@indtl@noautomatic
121     \addto@hook\toks@{\KV@indtl@noautomatictrue}%
122   \else
123     \addto@hook\toks@{\KV@indtl@noautomaticfalse}%
124   \fi
125   \ifKV@indtl@intoc
126     \addto@hook\toks@{\KV@indtl@intoctrue}%
127   \else
128     \addto@hook\toks@{\KV@indtl@intocfalse}%
129   \fi
130   \ifKV@indtl@columnseprule
131     \addto@hook\toks@{\KV@indtl@columnsepruletrue}%
132   \else
133     \addto@hook\toks@{\KV@indtl@columnseprulefalse}%
134   \fi
135   \expandafter\edef\csname indtl@set@#1\endcsname{\the\toks@}%
136 }

```

Command `\indtl@dokey` receives as argument the text of the values assigned to certain keys, and adds them to the options token list.

```

137 \def\indtl@dokey#1{%
138   \expandafter\addto@hook\expandafter\toks@\expandafter{%
139     \expandafter\def\expandafter#1\expandafter{#1}}

```

Command `\indtl@startidx` defines the output stream(s); the macro with suffix `split` is used when `splitindex` is not enabled, the one with suffix `unique` is used otherwise. In the case of many indices, the symbolic name for an index named ‘pippo’ is `\pippo@idxfile` corresponding to the file `pippo.idx`. When `splitindex` is enabled, the only output stream is called `\@indexfile` as in standard L<sup>A</sup>T<sub>E</sub>X, corresponding to `\jobname.idx`.

```

140 \def\indtl@startidxsplit#1{%
141   \if@filesw
142     \def\index{\@bsphack
143       \ifnextchar [{\@index}{\@index[\indtl@jobname]}}
144     \expandafter\newwrite\csname #1@idxfile\endcsname
145     \immediate\openout \csname #1@idxfile\endcsname #1.idx\relax
146     \typeout{Writing index file #1.idx}%
147   \fi}

```

We define a switch which is set to true when a `\makeindex` command is given: with `splitindex` we open only one stream.

```

148 \newif\ifindtl@startedidx
149 \def\indtl@startidxunique#1{%
150   \if@filesw
151     \ifindtl@startedidx\else
152       \newwrite\@indexfile
153       \immediate\openout\@indexfile\indtl@jobname.idx%
154       \global\indtl@startedidxtrue
155     \fi
156     \def\index{\@bsphack
157       \ifnextchar [{\@index}{\@index[\indtl@jobname]}}
158     \expandafter\let\csname #1@idxfile\endcsname\empty
159     \typeout{Started index file #1}%
160   \fi}

```

### 6.3 `\index`

Provide a default definition for `\index`; when a `\makeindex` command is given and L<sup>A</sup>T<sub>E</sub>X is writing on auxiliary files, `\index` will be redefined, as seen before. When index files are written, `\index` always calls `\@index`. Some code is borrowed from `memoir.cls`, but heavily modified. We want `\@windex` to be defined with two arguments, so that `hyperref` can hook into it just like it does with the similar commands defined by the old packages `multind` and `index`.

```

161 \renewcommand{\index}[2][\@bsphack\@esphack]
162 \def\@index[#1]{%
163   \@ifundefined{#1@idxfile}%
164   {\PackageWarning{indextools}{Undefined index file ‘#1’}%
165   \begingroup
166   \@sanitize
167   \indtl@nowrindex}%
168   {\edef\@idxfile{#1}%
169   \begingroup
170   \@sanitize

```

```

171 \@wrindex\@idxfile}}
172 \def\indtl@nowrindex#1{\endgroup\@esphack}

```

Command `\@wrindex` must be duplicated; we have to call it the same as usual in order to support `hyperref`. But the real name will be given at the end. We have to define a switch to allow the use of the `showidx` facilities. We define also a helper macro so as to do the right thing so as to show the index file name to which a certain index entry is going to be written; the idea is to prefix the index entry with the actual name of the specific index, except in the case of the default index, where the name is set to `\jobname`. Since the control sequence is a primitive command, its value cannot be directly compared in the `\ifx` sense to the current macro represented by argument #1. Therefore we need a further helper control sequence `\indtl@jobname` that contains the value assigned to `\jobname`.

We must also take care of the case where the user wants to print the index entries in the margin while working on the document. This implies testing for the package `showidx` being already loaded; but this is not sufficient, because the `memoir` class simulates the `showidx` package and the test would result to be true even if the user did not load that package, but uses the `memoir` class.

Therefore we use the same boolean used by `memoir`, testing in advance so as not redefining it; then we use it to let the `showidx` true or simulated macros do their job, but we also take care of resetting the switch default value to false at begin document time if the `memoir` class is being used.

```

173 \@ifundefined{showindexmarks}{\newif\ifshowindexmark}{-}
174 \@ifpackage{showidx}{\showindexmarktrue}{\showindexmarkfalse}
175 \newcommand\indtl@showidxentry[2]{%
176   \ifshowindexmark
177     \@showidx{\ifdefequal{\indtl@jobname}{#1}{\space}#2}%
178   \fi}
179 \newcommand\indtl@wrindexentrysplit[3]{%
180   \expandafter\protected@write\csname#1@idxfile\endcsname{%
181     {\string\indexentry{#2}{#3}}%
182 }
183 \newcommand\indtl@wrindexentryunique[3]{%
184   \protected@write\@indexfile{%
185     {\string\indexentry{#1}{#2}{#3}}%
186 }
187 \def\indtl@wrindexsplit#1#2{%
188   \indtl@wrindexentrysplit{#1}{#2}{\thepage}%
189 \endgroup\indtl@showidxentry{#1}{#2}%
190   \@esphack%
191 }
192 \def\indtl@wrindexunique#1#2{%
193   \indtl@wrindexentryunique{#1}{#2}{\thepage}%
194 \endgroup\indtl@showidxentry{#1}{#2}%
195   \@esphack%
196 }

```

## 6.4 `\printindex`

Compilation of the indices is disabled if `-shell-escape` has not been given or the restricted mode is not active; in this case we emit a warning.  $\TeX$  has `\shellescape` instead of `\pdfshellescape`, so we take care of this (hop-

ing that users or packages don't define a `\shellescape` command). In any case we define an internal version of this command. In the case of *luatex* we can't emit the proper messages if *luatex* is not version 0.68 or later. The conditional `\ifKV@indtl@noautomatic` is defined by `\define@boolkey` above.

```

197 \def\indtl@shellwarn{}
198 \ifdefined\indtl@shellescape % luatex
199 \else
200   \ifundefined{shellescape}
201     {\let\indtl@shellescape\pdfshellescape} % pdftex
202     {\let\indtl@shellescape\shellescape} % xetex
203 \fi
204 \ifnum\indtl@shellescape=\z@
205   \let\KV@indtl@noautomaticfalse\KV@indtl@noautomatictrue
206   \KV@indtl@noautomatictrue
207   \def\indtl@shellwarn{\MessageBreak or call \indtl@engine\space with
208     -shell-escape}
209 \fi

```

Do the same if *noautomatic* has been given as an option.

```

210 \ifindtl@disableautomatic
211   \let\KV@indtl@noautomaticfalse\KV@indtl@noautomatictrue
212   \KV@indtl@noautomatictrue
213 \fi

```

Now we set up the `theindex` environment. If the original option is set, we simply patch the class definition in order to call the macro that does the work related to the table of contents. Otherwise we define a new `theindex` environment, based on the standard, but using, if the number of columns is greater than one, the `multicols` environment. Users needing a different setup can use the `\indexsetup` command. Before doing so, though, we need to disable certain features if the package `fancyhdr` is loaded sometimes before the `\begin{document}` statement, be it before or after loading `indextools`. If that package is loaded we have to patch the definition of the environment `theindex`, because its default commands interfere with those defined here that work perfectly when `fancyhdr` is not loaded. This patching could be defined further on, but if it remains close to what has to be patched, it's easier to understand its operation.

We make this redefinition at the beginning of the document, to prevent redefinition by other packages, like `bidi`. This point is where `indextools` and `imakeidx` diverge.

```

214 \newif\ifindtl@fancyhdr
215 \AtBeginDocument{%
216   \@ifpackageloaded{fancyhdr}{\indtl@fancyhdrtrue}{\indtl@fancyhdrfalse}%
217   \ifindtl@original
218     \expandafter\def\expandafter\theindex\expandafter{\expandafter
219       \indtl@maybeaddtotoc\theindex}
220   \else
221     \renewenvironment{theindex}
222       {\indtl@maybeaddtotoc
223         \indtl@indexlevel{\indexname}%
224         \ifindtl@fancyhdr\else%
225           \indtl@indexheaders%
226           \thispagestyle{\indtl@firstpagestyle}%
227         \fi%

```

```

228     \ifnum\indtl@columns>\@ne
229         \columnsep \indtl@columnsep
230         \ifx\indtl@idxprologue\relax
231             \begin{multicols}{\indtl@columns}
232         \else
233             \begin{multicols}{\indtl@columns}[\indtl@idxprologue]
234         \fi
235     \else
236         \indtl@idxprologue
237     \fi
238     \global\let\indtl@idxprologue\relax
239     \parindent\z@
240     \parskip\z@ \@plus .3\p@\relax
241     \columnseprule \ifKV@indtl@columnseprule.4\p@\else\z@\fi
242     \raggedright
243     \let\item\@idxitem
244     \indtl@othercode}
245 \ifnum\indtl@columns>\@ne\end{multicols}\fi
246 }
247 \fi
248 }
249 \ifindtl@original
250 \else
251     \global\let\indtl@idxprologue\relax
252     \RequirePackage{multicol}
253 \fi

```

The command `\indexsetup` may be used to customize some aspects of index formatting.

```

254 \def\indtl@indexlevel{%
255     \@ifundefined{chapter}{\section}{\chapter}*}
256 \define@key{indtl@index}{level}{\def\indtl@indexlevel{#1}}
257 \def\indtl@toclevel{%
258     \@ifundefined{chapter}{section}{chapter}}
259 \define@key{indtl@index}{toclevel}{\def\indtl@toclevel{#1}}
260 \define@boolkey{indtl@index}{noclearpage}[true]{\let\indtl@clearpage\relax}
261 \def\indtl@indexheaders{%
262     \@mkboth{\MakeUppercase\indexname}{\MakeUppercase\indexname}}
263 \define@key{indtl@index}{headers}{\def\indtl@indexheaders{\markboth#1}}
264 \def\indtl@firstpagestyle{plain}
265 \define@key{indtl@index}{firstpagestyle}{\def\indtl@firstpagestyle{#1}}
266 \let\indtl@othercode\relax
267 \define@key{indtl@index}{othercode}{\def\indtl@othercode{#1}}
268 \newcommand{\indexsetup}[1]{%
269     \ifindtl@original\else\setkeys{indtl@index}{#1}\fi}
270 \@onlypreamble\indexsetup

```

The command `\indexprologue` sets the internal version which is always `\let` to `\relax` during `\begin{theindex}`.

```

271 \newcommand{\indexprologue}[2][\bigskip]{%
272     \long\gdef\indtl@idxprologue{#2\par#1}}

```

Now we provide the relevant `\printindex` macros by transferring the real job to a secondary macro `\indtl@putindex` after due checks and messages.

```

273 \providecommand*\printindex{}

```

```

274 \renewcommand*{\printindex}[1][\indtl@jobname]{%
275   \ifundefined{#1@idxfile}{\indtl@error{#1}}{\indtl@putindex{#1}}}
276
277 \def\indtl@error#1{%
278   \def\@tempa{#1}\def\@tempb{\indtl@jobname}%
279   \ifx\@tempa\@tempb
280     \let\indtl@optarg\@empty
281   \else
282     \def\indtl@optarg{[#1]}%
283   \fi
284   \PackageError{indextools}
285     {Misplaced \protect\printindex\indtl@optarg}
286     {You are not making this index, as no appropriate
287       \protect\makeindex\MessageBreak
288       command has been issued in the preamble.}}

```

We define a command to do a `\cleardoublepage` if the option *openright* is active (in classes where *twoside* is meaningful). In case `\chapter` is defined but not `\ifopenright`, we assume that the class wants “open right”.

```

289 \def\indtl@clearpage{%
290   \ifundefined{chapter}
291     {\clearpage} % article and similar classes
292   {\ifundefined{ifopenright}
293     {\cleardoublepage}
294     {\ifopenright
295       \cleardoublepage
296       \else
297         \clearpage
298       \fi}
299   }}

```

We need a helper macro to do a check in order to avoid a loop and the hook where to insert the table of contents related stuff.

```

300 \def\indtl@check@indexname{\indexname}
301 \providecommand*\indtl@maybeaddtotoc{}

```

Two helper macros for preparing the final messages to the user.

```

302 \def\indtl@finalmessage#1{%
303   \expandafter\edef\csname indtl@message#1\endcsname
304     {\indtl@program\indtl@options#1.idx}
305   \AtEndDocument{\PackageWarning{indextools}{%
306     Remember to run \indtl@engine\space again after calling\MessageBreak
307     ‘\@nameuse{indtl@message#1}’\indtl@shellwarn@gobble}}}}
308 \def\indtl@splitindexmessage{%
309   \AtEndDocument{\PackageWarningNoLine{indextools}{%
310     Remember to run \indtl@engine\space again after calling\MessageBreak
311     ‘splitindex’ and processing the indices\indtl@shellwarn}}}}

```

Here is a helper macro for deciding whether to call the external utility or to issue a final message. In `\indtl@makeindexname` we put the name of the only program allowed by default (*makeindex*). If the list is updated, we can supplement the list here, maybe defining a list macro; for now this is sufficient. The temporary switch `\if@tempswa` is set to true if automatic processing is possible, so that the main macro can take the appropriate action.

```

312   \def\indtl@makeindexname{makeindex}

```



```

313 \def\indtl@decide{%
314   \@tempswafalse
315   \ifindtl@splitindex % splitindex is not "safe"
316   \ifnum\indtl@shellescape=\@ne\@tempswatrue\fi
317   \else
318   \ifx\indtl@program\indtl@makeindexname % nor is texindy
319   \ifnum\indtl@shellescape=\tw@\@tempswatrue\fi
320   \fi
321   \ifnum\indtl@shellescape=\@ne\@tempswatrue\fi
322   \fi
323   \ifKV@indtl@noautomatic
324   \@tempswafalse
325   \fi}

```

We define a macro that close a specified index file and run in.

```

326 \newcommand{\indtl@closeandrundidxsplit}[1]{%
327   \immediate\closeout\csname #1idxfile\endcsname
328   \let\indtl@indexname\indexname % keep \indexname
329   \@nameuse{indtl@set@#1}\indtl@decide
330   \if@tempswa % we can call the external program
331   \indtl@exec{\indtl@program\indtl@options#1.idx}%
332   \else
333   \indtl@finalmessage{#1}%
334   \fi
335 }

```

We define a macro that close the general index file and run in.

```

336 \newcommand{\indtl@closeandrundidxunique}{%
337   \immediate\closeout\@indexfile
338   \indtl@exec{splitindex \indtl@splitindexoptions\space\indtl@jobname.idx}%
339   \global\indtl@splitdonetrue
340 }

```

We now define the main macro that puts the specified index file into the document and possibly orders to add the index title to the table of contents. It is duplicated as usual. The argument #1 is the specific symbolic name of the index. In particular if the *intoc* option has been specified, the hook `\indtl@maybeaddtotoc` is defined in such a way that the relevant information is added to the `toc` file. The `\phantomsection` command is necessary when using `hyperref`; here it is hidden as argument to `\@nameuse`, so it is equivalent to `\relax` and does nothing if `hyperref` has not been loaded.

```

341 \def\indtl@putindexsplit#1{%
342   \ifindtl@nonewpage\else
343   \indtl@clearpage
344   \fi
345   \ifindtl@afterindex%
346   \AtEndDocument{%
347     \indtl@clearpage%
348     \indtl@closeandrundidxsplit{#1}%
349     \indtl@afterindexMessage%
350   }%
351   \else%
352   \indtl@closeandrundidxsplit{#1}%
353   \fi
354   \ifKV@indtl@intoc

```

```

355     \def\indtl@maybeaddtotoc{\@nameuse{phantomsection}%
356         \addcontentsline{toc}{\indtl@toclevel}{\indtl@title}}%
357 \else
358     \def\indtl@maybeaddtotoc{}%
359 \fi
360 \ifx\indtl@title\indtl@check@indexname\else
361     \def\indexname{\indtl@title}%
362 \fi
363 \@input@{#1.ind}
364 \let\indexname\indtl@indexname % restore \indexname
365 }
366
367 \newif\ifindtl@splitdone
368 \def\indtl@putindexunique#1{%
369     \ifindtl@nonewpage\else
370         \indtl@clearpage
371     \fi
372     \let\indtl@indexname\indexname % keep \indexname
373     \@nameuse{indtl@set@#1}\indtl@decide
374     \if@tempswa % we can call the external program
375         \ifindtl@splitdone\else
376             \ifindtl@afterindex
377                 \AtEndDocument{%
378                     \indtl@clearpage%
379                     \indtl@closeandrundidxunique%
380                     \indtl@afterindexMessage%
381                 }
382             \else
383                 \indtl@closeandrundidxunique
384             \fi
385         \fi
386     \else
387         \ifindtl@splitdone\else
388             \indtl@splitindexmessage\global\indtl@splitdonetrue
389         \fi
390     \fi
391     \if@tempswa % we can call the external program
392         \indtl@exec{\indtl@program\indtl@options\indtl@jobname-#1.idx}%
393     \fi
394     \ifKV@indtl@intoc
395         \def\indtl@maybeaddtotoc{\@nameuse{phantomsection}%
396             \addcontentsline{toc}{\indtl@toclevel}{\indtl@title}}%
397     \else
398         \def\indtl@maybeaddtotoc{}%
399     \fi
400     \ifx\indtl@title\indtl@check@indexname\else
401         \def\indexname{\indtl@title}%
402     \fi
403     \@input@{\indtl@jobname-#1.ind}
404     \let\indexname\indtl@indexname % restore \indexname
405 }

```

A warning message when using ‘afterindex’ option.

```

406 \newcommand{\indtl@afterindexMessage}{%
407 \PackageWarning{indextools}{You use the ‘afterindex’ option.

```

```

408 \MessageBreak That means you use \string\index\space commands after \string\printindex\space
409 \MessageBreak Consequently, the index may be not ok at the first run.
410 }%
411 }

```

## 6.5 ‘innote’ and ‘notenumber’ options

If the ‘innote’ option is enabled, we modify the standard index command when we are in a note, in order to insert the |innote in the .idx file.

```

412
413 \AtBeginDocument{%
414   \ifindtl@innote%
415     \RequirePackage{letltxmacro}
416     \LetLtxMacro\orig@@index\index
417     \pretocmd{\@footnotetext}{\let\index\nindex}{-}{-}
418     \apptocmd{\@footnotetext}{\let\index\orig@@index}{-}{-}
419
420   \fi%

```

The same is true if the ‘notnumber’ option is enabled.

```

421   \ifindtl@notenumber%
422     \RequirePackage{letltxmacro}
423     \LetLtxMacro\orig@@index\index
424     \pretocmd{\@footnotetext}{\let\index\nnumberindex}{-}{-}
425     \apptocmd{\@footnotetext}{\let\index\orig@@index}{-}{-}
426   \fi%

```

```

427 % And now, the command, defines in any case, but only at the begin of documents, because people
428 \newcommand\nnumberindex[2][\indtl@jobname]{\orig@@index[#1]{#2|innotenumber{\thefootnote}}}
429 \newcommand\nindex[2][\indtl@jobname]{\orig@@index[#1]{#2|innote}}
430 \providecommand{\innotenumber}[2]{#2n.~#1}
431 \providecommand{\innote}[1]{#1\textit{n}}
432 }
433 % \end{macrocode}
434 % \subsection{Final decisions}
435 %
436 % At this point, we choose the meaning of the relevant commands,
437 % reclaiming the space occupied by the discarded ones
438 % \begin{macrocode}
439 \ifindtl@splitindex
440 \let\indtl@startidx\indtl@startidxunique
441 \let\@wrindex\indtl@wrindexunique
442 \let\indtl@putindex\indtl@putindexunique
443 \let\indtl@wrindexentry\indtl@wrindexentryunique
444 \let\indtl@startidxsplit\@undefined
445 \let\indtl@wrindexsplit\@undefined
446 \let\indtl@putindexsplit\@undefined
447 \else
448 \let\indtl@startidx\indtl@startidxsplit
449 \let\@wrindex\indtl@wrindexsplit
450 \let\indtl@putindex\indtl@putindexsplit
451 \let\indtl@wrindexentry\indtl@wrindexentrysplit
452 \let\indtl@startidxunique\@undefined
453 \let\indtl@wrindexunique\@undefined
454 \let\indtl@putindexunique\@undefined

```

```
455 \fi
```

To end the code, we deal with memoir:

```
456 \ifclassloaded{memoir}{\let\wrindexm@m\wrindex  
457   \AtBeginDocument{\hideindexmarks}}{}}
```

The end.