IEEE P1003.0 Draft 13 – September 1991

Copyright © 1991 by the
Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street
New York, NY 10017, USA
All rights reserved as an unpublished work.

This is an unapproved and unpublished IEEE Standards Draft, subject to change. The publication, distribution, or copying of this draft, as well as all derivative works based on this draft, is expressly prohibited except as set forth below.

Permission is hereby granted for IEEE Standards Committee participants to reproduce this document for purposes of IEEE standardization activities only, and subject to the restrictions contained herein.

Permission is hereby also granted for member bodies and technical committees of ISO and IEC to reproduce this document for purposes of developing a national position, subject to the restrictions contained herein.

Permission is hereby also granted to the preceding entities to make limited copies of this document in an electronic form only for the stated activities.

The following restrictions apply to reproducing or transmitting the document in any form: 1) all copies or portions thereof must identify the document's IEEE project number and draft number, and must be accompanied by this entire notice in a prominent location; 2) no portion of this document may be redistributed in any modified or abridged form without the prior approval of the IEEE Standards Department.

Other entities seeking permission to reproduce this document, or any portion thereof, for standardization or other activities, must contact the IEEE Standards Department for the appropriate license.

Use of information contained in this unapproved draft is at your own risk.

IEEE Standards Department
Copyright and Permissions
445 Hoes Lane, P.O. Box 1331
Piscataway, NJ 08855-1331, USA
+1 (908) 562-3800
+1 (908) 562-1571 [FAX]

# Section 3: POSIX Open System Environment

*Responsibility: Fritz Schulz*

The POSIX Open System Environment (OSE) is a collection of concepts that provide a context for user requirements and standards specification. It provides a minimum, standard set of conceptual information system building blocks with associated interfaces and functionality. The POSIX OSE consists of a reference model, service definitions, standards, and profiles.

These OSE concepts are also intended to be conventional within computer science. The intention is not to break new ground, but to establish a minimum and unambiguous terminology and set of concepts for identification and resolution of portability and interoperability issues.

The POSIX Open System Environment is defined in five parts:

(1) General requirements are identified that apply to the POSIX OSE as a whole in 3.1.

(2) A reference model is developed that unambiguously identifies the system under consideration for purposes of specification. The POSIX OSE reference model described in 3.2 defines system elements to identify interfaces across which service requirements should be satisfied. The elements are chosen to expose those interfaces that are significant to the profile writer or user.

(3) Using the interfaces identified in the reference models, each subclause of Section 4 categorizes and describes the basic services available to users across each interface. The services are defined in a generic way, based on the reference model, user requirements, and current industry practice, rather than any given implementation.

Definition of the service requirements is not constrained by the availability of standards. Service requirements that are not currently satisfied via standards are discussed in either the Emerging Standards subclause, or under Gaps.

Each clause of Section 4 begins with a more detailed and specialized version of the reference model to provide a context for service specification. After defining the interfaces and services, each of the Section 4 clauses concludes with a discussion of standards that are related to the services.

(4) Section 5 discusses issues and requirements that directly affect all of the service categories, such as internationalization, security, and

Copyright © 1991 IEEE. All rights reserved.
This is an unapproved IEEE Standards Draft, subject to change.

administration.

(5) Section 6 provides guidelines for creating profiles that address various application domains. This is a brief description of how the reference model and services are applied to a variety of existing types of systems. Section 7 describes current POSIX profiles and profiling activities.

The text emphasizes the concept of service requirements (rather than services) to emphasize that the POSIX OSE only includes requirements, not solutions which satisfy those requirements. It is the standards and profiles listed in the subclauses of Sections 4 and 5 that will satisfy these requirements.

Definition of the service requirements is not constrained by the availability of standards. Services requirements that are not currently satisfied via standards are discussed in either the Emerging Standards subclause, or under Gaps.

## 3.1 POSIX Open System Environment — General Requirements

The POSIX Open System Environment should satisfy the requirements in the following list:

(1) Application Portability at the Source Code Level

The POSIX OSE shall enable application software portability at the source code level.

Rationale: Comprehensive and consistent source code level service specifications allow porting of applications among processors (ideally without modification). Binary portability requires too tight a coupling with the processor implementation.

(2) System Interoperability

The POSIX OSE shall enable application software and system service interoperability.

Rationale: Communications services and format specifications allow two entities participating in a distributed system to exchange and make mutual use of data, including: D

— Homogeneous systems

— Heterogeneous systems (i.e., a wide variety of hardware/software platforms)

— POSIX-OSE-based and non-OSE-based systems

(3) User Portability

The POSIX OSE shall enable human users to operate on a wide range of systems without retraining.

Rationale: Standard methods and services for supporting human/computer interaction are a key aspect of the definition of an open

Copyright © 1991 IEEE. All rights reserved.
This is an unapproved IEEE Standards Draft, subject to change.